



EVG[®]101

Advanced Resist Processing System



Introduction

Single-wafer resist processing in R&D and small-scale production

The EVG101 resist processing system performs R&D-type processes on a single chamber design, which is fully compatible with EVG's automated systems. The EVG101 supports wafers up to 300 mm and can be configured for spin or spray coating and developing. Conformal layers of photoresist or polymers are achieved on 3D structured wafers for interconnection techniques with EVG's advanced OmniSpray coating technology. This ensures low material consumption of precious high-viscosity photoresists or polymers while improving uniformity and resist spreading options.

Technical Data	
Wafer diameter (substrate size)	up to 300 mm
Available modules	- Spin coat / OmniSpray [®] / develop
Wafer handling options	- Bowed / warped / thin wafer handling - Edge handling
Dispense options	- various resist dispense pumps to cover a wide range of viscosities up to 52000 cP - constant pressure dispense systems - EBR / BSR / pre-wet / bowl wash / liquid priming

Contact

EV Group Europe & Asia/Pacific GmbH
 DI Erich Thallner Strasse 1
 4782 St. Florian am Inn
 Austria
 +43 7712 5311 0

Contact@EVGroup.com



Features

- Wafer size up to 300 mm
- Automated spin or spray coating or developing with manual wafer load/unload
- Quick and easy process transfer from research to production utilizing proven modular design and standardized software
- Syringe dispense system for utilization of small resist volumes, including high-viscosity resists
- Small footprint while maintaining a high level of personal and process safety
- Multi-user concept (unlimited number of user accounts and recipes, assignable access rights, different user interface languages)
- Options:
 - Uniform coating of high-topography wafer surfaces with OmniSpray[®] coating technology
 - Wax and epoxy coating for subsequent bonding processes
 - Spin-On-Glass (SOG) coating

Printed on paper from sustainable sources. Data, design and specifications may not simultaneously apply, or depend on individual equipment configuration, process conditions and materials and may vary accordingly. EVG reserves the right to change data, design and specifications without prior notice. All trademarks, logos, website addresses or equipment names are registered trademarks and/or the property of EV Group or their respective owners. © EV Group (EVG). All rights reserved. V20/01

